

Tadiran CP920 HD IP Conference Phone

The Tadiran CP920 High Definition IP conference phone is a perfect choice for small and medium-sized conference rooms as it combines ease of use with the most sophisticated of features. The CP920 provides many important audio features including optima HD technology, full-duplex technology and a sensitive touch keypad. In addition, the CP920 incorporates a built in 3 microphone array and Noise Proof Technology for a 6 meter, 360 degree voice pickup range which will ensure the best conference call quality available.



Features:

- Optima HD voice, full duplex technology
- 20-feet and 360 degree voice pickup
- Noise Proof Technology
- Sensitive Touch Keypad
- Connect to a mobile phone or PC for conference calls
- USB call recording support
- Built in WiFi and Bluetooth 4.0

Specifications:

Audio Features:

- Optima HD voice
- 20-feet (6-meter) microphone pickup
- Built in 3-microphone array, 360 degree voice pickup
- 56 mm diameter and 5w speaker
- Full-duplex speakerphone with AEC
- Echo cancellation tail length is up to 320ms
- Background noise suppression
- Codecs: G.722, G722.1C, G726, G729, G723, iLBC, Opus, PCMA, PCMU
- DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO
- VAD, CNG,PLC, AJB, AGC

Phone Features:

- 1 VoIP account
- Call hold, mute, DND
- Call recording, hotline
- Redial, call waiting, emergency call
- Call forward, call transfer, call return, dial plan
- Ring tone selection/import/delete
- Pairing via Bluetooth
- Volume adjustment

Directory:

- Local phonebook up to 1000 entries
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export
- Call history:
dialed/received/missed/forwarded
- Black list

IP-PBX Features

- Intercom, multicast paging
- Anonymous call, anonymous call rejection
- Voice mail, distinctive ringtone, call pickup

Display:

- 3.1" 248x120 pixel graphical LCD with backlight
- 25 total keys
- Phone lock
- Multilingual user interface
- Caller ID with name and number
- LCD display

Interface:

- 1xRJ45 10/100M Ethernet port
- Power over Ethernet (IEEE 802.3af), class 3
- Built in WiFi (2.4 GHz, 802.11 b/g/n)
- Built in Bluetooth 4.0
- 1 x USB 2.0 port
- 1 x Security slot



Network and Security:

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP server redundancy supported
- IPv4/IPv6
- NAT transverse: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP
- SRTP for voice encryption
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X

Management:

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069, SNMP
- Reset to factory, reboot
- Package tracing export, system log

Other physical features:

- External power adaptor: AC 100~240V input and DC 12V/1A Output
- Power consumption (PoE): 3.9w - 7.6w
- Dimension(W*D*H): 307.8mm*298mm*66.9mm
- Operating humidity: 10~90%
- Storage temperature: -10~40°C

About Tadiran:

Tadiran Telecom (TTL) L.P. is a privately held partnership, owned by Afcon Holdings Ltd. and part of the Shlomo Group. It is an established global provider of Unified Communications & Collaboration (UC&C), Contact Center, and Control Room solutions, serving businesses of all sizes, including tier-1 organizations in various market segments in 41 countries worldwide. Tadiran solutions feature a comprehensive family of products including UC platforms, soft switches, contact centers, Dispatch Console, IP phones and mobility and desktop solutions.

Visit us at: www.tadirantele.com

Copyright © 2018 Tadiran Telecom (TTL) L.P. Specifications subject to change without notice. All other products or services mentioned are the trademarks, service marks, registered trademarks or registered service marks of their respective owners.

Israel +972-3-9262000

China +86-10-58696418

USA +1-678-506-7200

India +91-11-41523168/23353822